

**600V N-CHANNEL ENHANCEMENT MODE MOSFET**

**MAIN CHARACTERISTICS**

|                               |                    |
|-------------------------------|--------------------|
| $I_D$                         | 6A                 |
| $V_{DSS}$                     | 600V               |
| $R_{DS(on)-typ}(@V_{GS}=10V)$ | <1.7Ω (Type:1.4 Ω) |




**Features**

- ◆Fast Switching
- ◆Low ON Resistance
- ◆Low Gate Charge
- ◆100% Single Pulse avalanche energy Test
- ◆LeadfreeincomplywithEUroHS2011/65/EUdirectives

**Mechanical Data**

- ◆Case: Molded plastic
- ◆Mounting Position: Any
- ◆Molded Plastic: UL Flammability Classification Rating 94V-0
- ◆Solder bath temperature275°C maximum,10s per JESD22-106



**Product Specification Classification**

| Part Number | Package        | Marking           | Pack         |
|-------------|----------------|-------------------|--------------|
| YFW6N60AT   | TO-220AB       | YFW 6N60AT XXXXX  | 50PCS/Tube   |
| YFW6N60AF   | TO-220F(0.5mm) | YFW 6N60AF XXXXX  | 50PCS/Tube   |
| YFW6N60AS   | TO-263         | YFW 6N60AS XXXXX  | 50PCS/Tube   |
| YFW6N60AS-R | TO-263         | YFW 6N60AS XXXXX  | 800PCS/Tape  |
| YFW6N60AMJ  | TO-251         | YFW 6N60AMJ XXXXX | 80PCS/Tube   |
| YFW6N60AD   | TO-252         | YFW 6N60AD XXXXX  | 2500PCS/Tape |

**Maximum Ratings at Tc=25°C Unless Otherwise Specified**

| Characteristics                         | Symbols                | Value       |      |         | Units       |
|---|------------------------|-------------|------|---------|-------------|
|   |                        | 220AB/263   | 220F | 251/252 |             |
| Drain-Source Voltage                    | <b>V<sub>DS</sub></b>  | 600         |      |         | <b>V</b>    |
| Gate-Source Voltage                     | <b>V<sub>GS</sub></b>  | ±30         |      |         | <b>V</b>    |
| Continue Drain Current                  | <b>I<sub>D</sub></b>   | 6           |      |         | <b>A</b>    |
| - Continuous(Tc=100°C)                  |                        | 4           |      |         |             |
| Pulsed Drain Current (Note1)            | <b>I<sub>DM</sub></b>  | 24          |      |         | <b>A</b>    |
| Power Dissipation                       | <b>P<sub>D</sub></b>   | 85          | 22   | 75      | <b>W</b>    |
| -Derate above 25°C                      |                        | 0.63        | 0.32 | 0.64    |             |
| Single Pulse Avalanche Energy (Note2)   | <b>E<sub>AS</sub></b>  | 320         |      |         | <b>mJ</b>   |
| Avalanche Current (Note 1)              | <b>I<sub>AR</sub></b>  | 6           |      |         | <b>A</b>    |
| Repetitive Avalanche Energy (Note 1)    | <b>E<sub>AR</sub></b>  | 11          |      |         | <b>mJ</b>   |
| Operating Temperature Range             | <b>T<sub>J</sub></b>   | 150         |      |         | <b>°C</b>   |
| Storage Temperature Range               | <b>T<sub>STG</sub></b> | -55 to +150 |      |         | <b>°C</b>   |
| Thermal Resistance, Junction to Case    | <b>R<sub>θJC</sub></b> | 1.67        | 5.7  | 1.7     | <b>°C/W</b> |
| Thermal Resistance, Junction to Ambient | <b>R<sub>θJA</sub></b> | 62.5        | 62.5 | 100     | <b>°C/W</b> |

**Maximum Ratings at Tc=25°C unless otherwise specified**

| Characteristics                           | Test Condition   | Symbols                              | Min | Typ  | Max  | Units       |
|---|--|--------------------------------------|-----|------|------|-------------|
| Drain-Source Breakdown Voltage            | V <sub>GS</sub> = 0 V, I <sub>D</sub> = 250 μA                                   | <b>BV<sub>DSS</sub></b>              | 600 | -    | -    | <b>V</b>    |
| Breakdown Voltage Temperature Coefficient | I <sub>D</sub> =250μA<br>(Referenced to 25°C)                                    | $\frac{\Delta BV_{DSS}}{\Delta T_J}$ | -   | 0.5  | -    | <b>V/°C</b> |
| Drain-Source Leakage Current              | V <sub>DS</sub> = 600 V, V <sub>GS</sub> = 0 V                                   | <b>I<sub>DSS</sub></b>               | -   | -    | 1    | <b>uA</b>   |
|   | V <sub>DS</sub> =480V, Tc=125°C  |                                      | -   | -    | 10   |             |
| Gate Leakage Current                      | V <sub>GS</sub> = ± 30 V, V <sub>DS</sub> = 0 V                                  | <b>I<sub>GSS</sub></b>               | -   | -    | ±100 | <b>nA</b>   |
| Gate-Source Threshold Voltage             | V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = 250 μA                      | <b>V<sub>GS(th)</sub></b>            | 3   | -    | 4    | <b>V</b>    |
| Drain-Source On-State Resistance          | V <sub>GS</sub> = 10 V, I <sub>D</sub> = 3 A                                     | <b>R<sub>DS(on)</sub></b>            | -   | 1.4  | 1.7  | <b>Ω</b>    |
| Forward Transconductance                  | V <sub>DS</sub> = 15 V, I <sub>D</sub> = 3A                                      | <b>g<sub>fs</sub></b>                | -   | 3.9  | -    | <b>S</b>    |
| Input Capacitance                         | V <sub>GS</sub> = 0 V, V <sub>DS</sub> = 25 V,<br>f = 1MHz                       | <b>C<sub>iss</sub></b>               | -   | 700  | -    | <b>pF</b>   |
| Output Capacitance                        |  | <b>C<sub>oss</sub></b>               | -   | 28.4 | -    |             |
| Reverse Transfer Capacitance              |  | <b>C<sub>rss</sub></b>               | -   | 5.8  | -    |             |
| Turn-on Delay Time                        | I <sub>D</sub> = 4 A, V <sub>DD</sub> = 300 V,<br>R <sub>G</sub> = 10 Ω(Note3.4) | <b>td(ON)</b>                        | -   | 13.9 | -    | <b>nS</b>   |
| Rise Time                                 |  | <b>tr</b>                            | -   | 19.9 | -    |             |
| Turn-Off Delay Time                       |  | <b>td(OFF)</b>                       | -   | 27.3 | -    |             |
| Fall Time                                 |  | <b>tf</b>                            | -   | 9.1  | -    |             |
| Total Gate Charge                         | I <sub>D</sub> = 4A, V <sub>DD</sub> = 480 V,<br>V <sub>GS</sub> = 10 V(Note3.4) | <b>Q<sub>G</sub></b>                 | -   | 11.5 | -    | <b>nC</b>   |
| Gate to Source Charge                     |  | <b>Q<sub>GS</sub></b>                | -   | 3.6  | -    |             |
| Gate to Drain Charge                      |  | <b>Q<sub>GD</sub></b>                | -   | 4    | -    |             |

**Source-Drain Diode Characteristics at Ta=25°C unless otherwise specified**







| Characteristics                          | Test Condition   | Symbols               | Min | Typ | Max | Units     |
|--|--|-----------------------|-----|-----|-----|-----------|
| Maximum Body-Diode Continuous Current    |  | <b>I<sub>S</sub></b>  | -   | -   | 6   | <b>A</b>  |
| Maximum Body-Diode Pulsed Current(Note2) |  | <b>I<sub>SM</sub></b> | -   | -   | 24  | <b>A</b>  |
| Drain-Source Diode Forward Voltage       | $I_{SD} = 4 \text{ A}$   | <b>V<sub>SD</sub></b> | -   | -   | 1.5 | <b>V</b>  |
| Reverse Recovery Time                    | $I_{SD} = 4 \text{ A}, V_{GS} = 0 \text{ V},$<br>$dI_F / dt = 100 \text{ A}/\mu\text{s}$ | <b>trr</b>            | -   | 240 | -   | <b>nS</b> |
| Reverse Recovery Charge                  |  | <b>Qrr</b>            | -   | 0.9 | -   | <b>uC</b> |

Note:

1. Repetitive Rating: Pulse width limited by maximum junction temperature.
2. IAS = 6 A, VDD = 50 V, L = 18mH, RG = 25Ω, starting TJ = 25°C.
3. ulse test: Pulse Width  $\leq 300 \mu \text{ s}$ , Duty Cycle  $\leq 2\%$ .
4. Essentially Independent of Operating Temperature.

Ratings and Characteristic Curves

**Maximum Safe Operating Area**



Package Outline Dimensions Millimeters

**TO-220AB**

| Dim.                         | Min.     | Max.  |
|------------------------------|----------|-------|
| A                            | 10.15    | 10.35 |
| B                            | 2.65     | 2.95  |
| C                            | 3.70     | 3.90  |
| D                            | 28.5     | 29.5  |
| E                            | 1.30     | 1.45  |
| F                            | 6.35     | 6.55  |
| G                            | 2.9      | 3.3   |
| H                            | 15.0     | 16.0  |
| I                            | 0.38     | 0.42  |
| J                            | 4.45     | 4.55  |
| K                            | 1.25     | 1.35  |
| L                            | Typ 5.08 |       |
| M                            | Typ 2.54 |       |
| N                            | 3.1      | 3.3   |
| O                            | 0.76     | 0.84  |
| All Dimensions in millimeter |          |       |

**TO-220F**

| Dim.                         | Min.     | Max.  |
|------------------------------|----------|-------|
| A                            | 9.95     | 10.25 |
| B                            | 2.95     | 3.25  |
| C                            | 1.25     | 1.45  |
| D                            | 12.95    | 13.25 |
| E                            | 0.50     | 0.65  |
| F                            | 3.1      | 3.3   |
| G                            | 1.30     | 1.45  |
| H                            | Typ 2.54 |       |
| I                            | Typ 5.08 |       |
| J                            | 4.60     | 4.75  |
| K                            | 2.50     | 2.65  |
| L                            | 6.35     | 6.55  |
| M                            | 15.4     | 16.0  |
| N                            | 2.75     | 3.05  |
| O                            | 0.48     | 0.52  |
| P                            | 0.76     | 0.84  |
| All Dimensions in millimeter |          |       |

Package Outline Dimensions Millimeters

**TO-263**

|                              |      |         |      |
|------------------------------|------|---------|------|
|                              | Dim. | Min.    | Max. |
|                              | A    | 10.1    | 10.2 |
|                              | B    | 7.4     | 7.6  |
|                              | C    | 1.3     | 1.5  |
|                              | D    | 0.55    | 0.75 |
|                              | E    | 5.0     | 6.0  |
|                              | F    | 1.4     | 1.6  |
|                              | G    | 0.78    | 0.86 |
|                              | H    | 1.2     | 1.3  |
|                              | I    | Typ2.54 |      |
|                              | J    | 8.4     | 8.6  |
|                              | K    | 4.45    | 4.55 |
|                              | L    | 1.25    | 1.35 |
|                              | M    | 0.02    | 0.1  |
| N                            | 2.4  | 2.8     |      |
| O                            | 0.36 | 0.40    |      |
| All Dimensions in millimeter |      |         |      |

**TO-252**

|                              |      |         |      |       |
|------------------------------|------|---------|------|-------|
|                              | Dim. | Min.    | Typ. | Max.  |
|                              | A    | 2.10    | -    | 2.50  |
|                              | A2   | 0       | -    | 0.10  |
|                              | B    | 0.66    | -    | 0.86  |
|                              | B2   | 5.18    | -    | 5.48  |
|                              | C    | 0.40    | -    | 0.60  |
|                              | C2   | 0.44    | -    | 0.58  |
|                              | D    | 5.90    | -    | 6.30  |
|                              | D1   | 5.30REF |      |       |
|                              | E    | 6.40    | -    | 6.80  |
|                              | E1   | 4.63    | -    | -     |
|                              | G    | 4.47    | -    | 4.67  |
|                              | H    | 9.50    | -    | 10.70 |
|                              | L    | 1.09    | -    | 1.21  |
| L2                           | 1.35 | -       | 1.65 |       |
| V1                           | -    | 7°      | -    |       |
| V2                           | 0°   | -       | 6°   |       |
| All Dimensions in millimeter |      |         |      |       |

Package Outline Dimensions Millimeters

TO-251

|                              |      |         |      |
|------------------------------|------|---------|------|
|                              | Dim. | Min.    | Max. |
|                              | A    | 2.2     | 2.4  |
|                              | A2   | 0.95    | 1.15 |
|                              | A3   | 0.45    | 0.65 |
|                              | b    | 0.65    | 0.85 |
|                              | c    | 0.45    | 0.55 |
|                              | D    | 6.45    | 6.75 |
|                              | D2   | 5.2     | 5.4  |
|                              | E    | 5.8     | 6    |
|                              | E2   | 0.95    | 1.25 |
|                              | e    | Typ 2.3 |      |
|                              | e1   | Typ 4.6 |      |
|                              | L    | 4       | 4.2  |
|                              | L1   | 1.2     | 1.5  |
| All Dimensions in millimeter |      |         |      |